



**Catalogue**  
**FOOD SERVICE**  
**Chapter**  
**REFRIGERATION**

**Specific model**  
**AEP-451**

19059668

30/04/2021

**DENOMINATION:**


Professional display refrigerated cabinet with 3+1 shelves.

**DESCRIPTION :**

Professional display refrigerated cabinet:

- Steel sheet exterior with white epoxy coating that provides high resistance to impacts and daily use.
- Inner body in food-standard ABS material.
- Interior corners and edges rounded to facilitate cleaning.
- Equipped with inner fluorescent lighting to help display and draw attention to your products.
- Double glazed door with handle incorporated into the frame
- Reversible door with frame manufactured in aluminium, providing it with an elegant and very aesthetically pleasing finish.
- Equipped with lock and key as standard.
- Digital thermometer with temperature control.
- Operational voltage: 230 V - 50 Hz.
- Guides inbuilt into the sides of the cabinet with anti-tip system.
- Drain inside the chamber.
- Forced refrigeration. Evaporator integrated into the back wall of the cabinet. A fan distributes the cold, obtaining a uniform temperature inside.
- R-600a hydrocarbon refrigerant gas.
- Operational temperature: -1 °C ÷ +6 °C, Ambient temperature 32 °C.

**DIMENSIONS**



X Width	626 mm	X Gross width	666 mm
Y Depth	740 mm	Y Gross depth	780 mm
Z Height	1865 mm	Z Gross height	2010 mm
Net Weight	82,0 kg	Gross Weight	93,0 kg
Net volume	0,864 m3	Gross volume	1,044 m3

**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	0,193 kW
Amperage (A)	1.3A
Voltage	230V - 1N
Electric frequency	50Hz

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Refrigeration power	0,292 kW
Climate class	4
Cooling gas load	81,000 g

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

**OTHERS**

Condensation system	Static
---------------------	--------



Catalogue  
**FOOD SERVICE**

Capítulo  
**REFRIGERATION**

Modelo  
**AEP-451**

19059668

30/04/2021

