



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
EAEP-1602 CR 230V 1N 50Hz

19037843

30/04/2021

DENOMINATION:

Refrigerated display cabinet - Concept Monoblock Gastronorm with 2 compartments and 2 doors, at 50Hz.

DESCRIPTION :

- Constructed with AISI-304 stainless steel.
 - 60 mm, 40 kg/m3 injected polyurethane insulation.
 - Embedded inner tray slides. Storage trays at 24 different levels 55 mm from each other.
 - Forced draught cooling system with hermetically sealed compressor.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Working temperature: from -2 °C to +8 °C(refrigerators) and from -18 °C to -22 °C (freezers).
 - Ambient temperature: 43 °C (AMBIENT TEMPERATURE: Guaranteed operation at 43°C. Excluded display models with glass doors. For specific intensive usage please check with Fagor Commercial Manager.)
 - Climatic class 4.
 - Inner LED lights with power switch (in refrigerated cabinets and now also in freezing units).
- Freezer cabinet.
 Visibility: vertical LED light for greater visibility.

POSSIBLE OPTIONS :

- Butcher Bar
- HACCP alarm
- Pedal
- Wheels Kit (Factory Assembly)
- Stainless Backing
- Door frame resistance

STANDARD OPTIONS :

- Locks


POSSIBLE ACCESSORIES :

- REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12037958 GN-2/1 Grill in Epoxy 650X530mm 6

DIMENSIONS



X Width	1318 mm	X Gross width	1430 mm
Y Depth	842 mm	Y Gross depth	880 mm
Z Height	2040 mm	Z Gross height	2063 mm
Net Weight	236,0 kg	Gross Weight	250,0 kg
Net volume	2,264 m3	Gross volume	2,596 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,212 kW
Amperage (A)	0,84 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,436 kW
Gross internal volume	1332 L
Climate class	4
Cooling gas load	100,000 g

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	2
Condensation system	Vent.



Catalogue
FOOD SERVICE

Capítulo
REFRIGERATION

Modelo
EAEP-1602 CR 230V 1N 50Hz

19037843

30/04/2021

