



**Catalogue**  
**FOOD SERVICE**  
**Chapter**  
**REFRIGERATION**

**Specific model**  
**EERMU-250 SS R-600a 230V 50Hz 1N**

19048292

30/04/2021

**DENOMINATION:**

Refrigerated wall displays ERMU series (exterior in stainless steel), height 800 mm with 2 doors.

**DESCRIPTION :**

Refrigerated wall displays ERMU SERIES (exterior in stainless steel): HEIGHT 800 mm

- Sanitary epoxy coated galvanised steel inside.
- Two outside finish options: either satin stainless steel (Inox version) or black plastic covered galvanised steel (black version).
- 40 kg/m<sup>3</sup> injected polyurethane insulation.
- Copper piping and aluminium flaps evaporator.
- Hermetically sealed copper serpentine ventilated compressor.
- Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.
- Digital display for electronic control of temperature.
- ON/OFF power switch.
- Top horizontal lightning.
- Working temperature: +2 °C, +8 °C (room temperature: 32 °C).

**STANDARD OPTIONS :**

- Locks

**DIMENSIONS**



X Width	925 mm	X Gross width	970 mm
Y Depth	565 mm	Y Gross depth	615 mm
Z Height	800 mm	Z Gross height	955 mm
Net Weight	80,0 kg	Gross Weight	83,0 kg
Net volume	0,418 m <sup>3</sup>	Gross volume	0,570 m <sup>3</sup>

**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	0,150 kW
Amperage (A)	0,93A
Voltage	230V - 1N
Electric frequency	50Hz

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Refrigeration power	0,167 kW
Climate class	4
Cooling gas load	44,000 g

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------

**OTHERS**

Number of doors	2
Condensation system	Vent.



Catalogue  
**FOOD SERVICE**

Capítulo  
**REFRIGERATION**

Modelo  
**EERMU-250 SS R-600a 230V 50Hz 1N**

19048292

30/04/2021

