

PM Pack A/S Satellitvej 7 DK-8700 Horsens Tlf. +45 75 60 20 00 Fax. +45 75 60 16 60 CVR-NR. 27 63 85 89 mail@pmpack.dk

www.pmpack.dk

TECHNICAL DATA SHEET	Page 1/1
Product:	
EMBOSSED COOKING BAGS FILM	
EMBOSSED SIDE	

<u>Description:</u> Medium barrier plastic film made of polyamide and polyethylene

sealing layer. The material is worked with an embossing process so

to create a special design which helps vacuum operations.

<u>Applications:</u> The film is especially designed for production of embossed vacuum

pouch to be used with most common models of external clamp type vacuum machines which are not able to work properly with standard pouches. Due to the large variety of models and performances of vacuum machines present on the market, we suggest to test the material in your standard working conditions

before placing an industrial order#.

Thanks to the selected raw materials used, this special pouch can stand ordinary thermal process or cooking conditions up to a

temperature of 115°C for no longer than 2 hrs.

Properties	Unit	Method	Value	Tolerance
Thickness of film before embossing process	microns	Internal method	105	+/- 10%
Weight per unit area of embossed film	g/m²	Internal method	105,9	+/- 10%
Oxygen permeability*	cc/m ² 24h	DIN 53380 23°C 75% U.R.	40	/
Nitrogen permeability*	cc/m ² 24h	DIN 53380 23°C 75% U.R.	/	/
Carbon dioxide	cc/m ² 24h	DIN 53380		/
permeability*		23°C 75% U.R.	/	
Temperature of use (min-max)	°C		-40/+115	/

^{*}Theoretical values

Material must be stored away from sunlight and in a clean place. Temperature must be kept between 15°C and 25°C with relative humidity between 50 and 75 %.

Material supplied complies with regulation EC 10/2011, regulation 1935/2004/EC and subsequent amendments.

All values mentioned are at the best of our knowledge. The application, use and processing of the products are beyond our control, and therefore, under the entire responsability of the user who is recommended to test the material in the most appropriate working conditions before placing industrial orders.

SALG OG SERVICE AF:

Flowpakkemaskiner Dybtrækmaskiner Traysealere Vejesystemer Krympepakkeanlæg Vertikale posepakkemaskiner Vacuumpakkemaskiner EMBALLAGE:

Vacuum-, kogesamt krympeposer Flexible folier Krympefolier Micro- og macro OPP folier ${\sf SALGS-OG\ LEVERINGSBETINGELSER:}$

For alle leverancer af nye og brugte maskiner samt emballage er omstående salgs- og leveringsbetingelser gældende. BANK:

Danske Bank A/S Copenhagen Reg. nr.: 4597 Konto nr.: 4354621 IBAN: 6430000004354621 SWIFT-BIC: DABADKKK

